



GENEREL INFORMATION	CIRCLE 200	CIRCLE 250	CIRCLE 300
Systemeffekt:	18W	29W	38W
Farvetemperatur:	3000K	3000K	3000K
Total lysstrøm:	1100 lm	1800 lm	2600 lm
Armaturvirkningsgrad:	61lm/W	62lm/W	68lm/W
Armaturfarve:	<input type="checkbox"/> H <input type="checkbox"/> G	<input type="checkbox"/> H <input type="checkbox"/> G	<input type="checkbox"/> H <input type="checkbox"/> G
Armaturmateriale:	Plast/akryl	Plast/akryl	Plast/akryl
Omgivelsestemperatur:	-20°~40°	-20°~40°	-20°~40°
Kapslingsklasse:	IP44	IP44	IP44
Vandklasse:	IK10	IK10	IK10
Isolationsklasse:	Klasse II	Klasse II	Klasse II
Netfrekvens:	50Hz	50Hz	50Hz
Ra-værdi:	>80	>80	>80
Spænding:	220-240VAC	220-240VAC	220-240VAC
Effektfaktor:	>0,85	>0,85	>0,85
Driver:	Integreret	Integreret	Integreret
Dæmpning:	Nej	Nej	Nej
Middellevetid L70B50:	50.000 timer	50.000 timer	50.000 timer
Dimensioner:	H:40 x Ø:200	H:43 x Ø:250	H:43 x Ø:300
Montage:	Væg/loft	Væg/loft	Væg/loft
Ledningstværsnit:	Max 0,75mm ²	Max 0,75mm ²	Max 0,75mm ²
Sløjfning:	Nej	Nej	Nej
Produkt nr:	3000K 27-0300-000001	27-0300-000002	27-0300-000003

Armaturet må kun anvendes som indendørsbelysning



MÅL OG SPECIFIKATIONER

