



FLOW ROUND

GENEREL INFORMATION

Systemeffekt:		12W	14W	18W	24W	28W
Farvetemperatur:		3000 / 4000K	3000 / 4000K	3000 / 4000K	3000 / 4000K	3000 / 4000K
Total lysstrøm:		800lm	1000lm	1400lm	1600lm	1700lm
Armaturfarve:		<input type="checkbox"/> H <input type="checkbox"/> A	<input type="checkbox"/> H <input type="checkbox"/> A	<input type="checkbox"/> H <input type="checkbox"/> A	<input type="checkbox"/> H <input type="checkbox"/> A	<input type="checkbox"/> H <input type="checkbox"/> A
Armaturmateriale:		Alu/plast/akryl	Alu/plast/akryl	Alu/plast/akryl	Alu/plast/akryl	Alu/plast/akryl
Kapslingsklasse:		IP44	IP44	IP44	IP44	IP44
Netfrekvens:		50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Ra værdi:		85	85	85	85	85
Spænding:		220-240V	220-240V	220-240V	220-240V	220-240V
Dæmpbar:		Nej	Nej	Nej	Nej	Nej
Driver:		Indbygget	Indbygget	Indbygget	Indbygget	Indbygget
Middellevetid:		50.000 timer	50.000 timer	50.000 timer	50.000 timer	50.000 timer
Dimensioner (mm):		H:80 x Ø:115	H:80 x Ø:125	H:80 x Ø:145	H:80 x Ø:165	H:80 x Ø:195
Produkt nr:	Hvid / 3000K	27-0240-000198	27-0240-000202	27-0240-000206	27-0240-000210	27-0240-000214
	Hvid / 4000K	27-0240-000199	27-0240-000203	27-0240-000207	27-0240-000211	27-0240-000215
	Alu / 3000K	27-0240-000200	27-0240-000204	27-0240-000208	27-0240-000212	27-0240-000216
	Alu / 4000K	27-0240-000201	27-0240-000205	27-0240-000209	27-0240-000213	27-0240-000217



LIGHT INNOVATION TECHNOLOGY