



FLOW SQUARE

GENEREL INFORMATION

Systemeffekt:	12W	14W	18W	24W	28W	
Farvetemperatur:	3000 / 4000K	3000 / 4000K	3000 / 4000K	3000 / 4000K	3000 / 4000K	
Total lysstrøm:	800lm	1000lm	1400lm	1600lm	1700lm	
Armaturfarve:	<input type="checkbox"/> H	<input type="checkbox"/> H	<input type="checkbox"/> H	<input type="checkbox"/> H	<input type="checkbox"/> H	
Armaturmateriale:	Alu/plast/akryl	Alu/plast/akryl	Alu/plast/akryl	Alu/plast/akryl	Alu/plast/akryl	
Kapslingsklasse:	IP44	IP44	IP44	IP44	IP44	
Netfrekvens:	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	
Ra værdi:	85	85	85	85	85	
Spænding:	220-240V	220-240V	220-240V	220-240V	220-240V	
Dæmpbar:	Nej	Nej	Nej	Nej	Nej	
Driver:	Indbygget	Indbygget	Indbygget	Indbygget	Indbygget	
Middellevetid:	50.000 timer	50.000 timer	50.000 timer	50.000 timer	50.000 timer	
Dimansjoner (mm):	L:115 x H:80 x W:115	L:125 x H:80 x W:125	L:145 x H:80 x W:145	L:165 x H:80 x W:165	L:195 x H:80 x W:195	
Produkt nr:	3000K 4000K	27-0240-000188 27-0240-000189	27-0240-000190 27-0240-000191	27-0240-000192 27-0240-000193	27-0240-000194 27-0240-000195	27-0240-000196 27-0240-000197



LIGHT INNOVATION TECHNOLOGY