



## GENEREL INFORMATION

Systemeffekt:		10W
Farvetemperatur:		2700K / 3000K / 4000K
Total lysstrøm:		570lm (2700K/3000K) / 620lm (4000K)
Armaturvirkningsgrad:		62lm/W (4000K)
Armaturfarve:		<input checked="" type="checkbox"/> S <input type="checkbox"/> H
Spredningsvinkel:		30°*
Armatur materiale:		Aluminium
Omgivelsestemperatur:		Max 35°
Kapslingsklasse:		IP20
Netfrekvens:		50Hz
Spænding:		220-240VAC
Energiklasse:		A++-A
Farvegengivelse:		CRI >90
Driver:		Integreret
Dæmpning:		Ja
Dæmpemetode:		DALI
Middellevetid L80B10:		50.000 timer
Vægt:		0,82 kg
Dimensioner (mm):		L:100 x B:100 x H:130
Montage:		Direkte på loft eller væg
Produkt nummer:	Hvid / 2700K Hvid / 3000K Hvid / 4000K Sort / 2700K Sort / 3000K Sort / 4000K	24-0300-000001 24-0300-000002 24-0300-000003 24-0300-000004 24-0300-000005 24-0300-000006

\*Kan på forespørgsel bestilles med spredningsvinkel 15° eller 45°+15°



# MÅL OG SPECIFIKATIONER

