



## LOGOUT DOWN

### GENEREL INFORMATION

Systemeffekt:	20W	26W	32W	52W	64W	78W	96W
Farvetemperatur:	3000 / 4000K	3000 / 4000K	3000 / 4000K	3000 / 4000K	3000 / 4000K	3000 / 4000K	3000 / 4000K
Total lysstrøm:	1350lm	1800lm	2250lm	3600lm	4500lm	5400lm	6750lm
Armaturfarbe:	<input type="checkbox"/> H <input checked="" type="checkbox"/> S <input type="checkbox"/> A	<input type="checkbox"/> H <input checked="" type="checkbox"/> S <input type="checkbox"/> A	<input type="checkbox"/> H <input checked="" type="checkbox"/> S <input type="checkbox"/> A	<input type="checkbox"/> H <input checked="" type="checkbox"/> S <input type="checkbox"/> A	<input type="checkbox"/> H <input checked="" type="checkbox"/> S <input type="checkbox"/> A	<input type="checkbox"/> H <input checked="" type="checkbox"/> S <input type="checkbox"/> A	<input type="checkbox"/> H <input checked="" type="checkbox"/> S <input type="checkbox"/> A
Cover:	Mikroprismatisk / opal	Mikroprismatisk / opal	Mikroprismatisk / opal	Mikroprismatisk / opal	Mikroprismatisk / opal	Mikroprismatisk / opal	Mikroprismatisk / opal
Kapslingsklasse:	IP20	IP20	IP20	IP20	IP20	IP20	20
CRI:	>80	>80	>80	>80	>80	>80	>80
Spænding:	220-240VAC	220-240VAC	220-240VAC	220-240VAC	220-240VAC	220-240VAC	220-240VAC
Energiforbrug:	22kW pr. 1000t	26kW pr. 1000t	36kW pr. 1000t	58kW pr. 1000t	71kW pr. 1000t	86kW pr. 1000t	106kW pr. 1000t
Dæmpbar:	Ja	Ja	Ja	Ja	Ja	Ja	Ja
Dæmpemethode:	1-10V (DALI ved bestilling)	1-10V (DALI ved bestilling)	1-10V (DALI ved bestilling)	1-10V (DALI ved bestilling)	1-10V (DALI ved bestilling)	1-10V (DALI ved bestilling)	1-10V (DALI ved bestilling)
Størrelse (mm):	L:870 x H:90 x W:60	L:1156 x H:90 x W:60	L:1441 x H:90 x W:60	L:2299 x H:90 x W:60	L:2869 x H:90 x W:60	L:3442 x H:90 x W:60	L:4297 x H:90 x W:60

#### Produkt nr:

##### Mikroprismatisk cover

Hvid / 3000K	24-0200-002113	24-0200-002119	24-0200-002125	24-0200-002131	24-0200-002137	24-0200-002143	24-0200-002149
Sort / 3000K	24-0200-002114	24-0200-002120	24-0200-002126	24-0200-002132	24-0200-002138	24-0200-002144	24-0200-002150
Alu / 3000K	24-0200-002115	24-0200-002121	24-0200-002127	24-0200-002133	24-0200-002139	24-0200-002145	24-0200-002151
Hvid / 4000K	24-0200-002116	24-0200-002122	24-0200-002128	24-0200-002134	24-0200-002140	24-0200-002146	24-0200-002152
Sort / 4000K	24-0200-002117	24-0200-002123	24-0200-002129	24-0200-002135	24-0200-002141	24-0200-002147	24-0200-002153
Alu / 4000K	24-0200-002118	24-0200-002124	24-0200-002130	24-0200-002136	24-0200-002142	24-0200-002148	24-0200-002154

##### Opal cover

Hvid / 3000K	24-0200-000113	24-0200-000119	24-0200-000125	24-0200-000131	24-0200-000137	24-0200-000143	24-0200-000149
Sort / 3000K	24-0200-000114	24-0200-000120	24-0200-000126	24-0200-000132	24-0200-000138	24-0200-000144	24-0200-000150
Alu / 3000K	24-0200-000115	24-0200-000121	24-0200-000127	24-0200-000133	24-0200-000139	24-0200-000145	24-0200-000151
Hvid / 4000K	24-0200-000116	24-0200-000122	24-0200-000128	24-0200-000134	24-0200-000140	24-0200-000146	24-0200-000152
Sort / 4000K	24-0200-000117	24-0200-000123	24-0200-000129	24-0200-000135	24-0200-000141	24-0200-000147	24-0200-000153
Alu / 4000K	24-0200-000118	24-0200-000124	24-0200-000130	24-0200-000136	24-0200-000142	24-0200-000148	24-0200-000154



LIGHT INNOVATION TECHNOLOGY