



INDENDØRS / PÅBYGGET / VÆGMONTERET



REGATO SURFACE



LIGHT INNOVATION TECHNOLOGY

LITE A/S. Østre Fælledvej 11, 9400 Nørresundby. www.lite-led.dk. t: +45 88 72 88 02. m: info@lite-led.dk.

REGATO SURFACE



GENEREL INFORMATION

	REGATO 350	REGATO 600	REGATO 900	
Systemeffekt:	21W	67W	135W	
Farvetemperatur:	3000K / 4000K	3000K / 4000K	3000K / 4000K	
Total lysstrøm:	1620lm (3000K) / 1800lm (4000K)	5270lm (3000K) / 5860lm (4000K)	11.080lm (3000K) / 12.190lm (4000K)	
Armaturvirkningsgrad:	86lm/W (4000K)	87lm/W (4000K)	90lm/W (4000K)	
Armaturfarve:	<input type="checkbox"/> S <input type="checkbox"/> H	<input type="checkbox"/> S <input type="checkbox"/> H	<input type="checkbox"/> S <input type="checkbox"/> H	
Armatur materiale:	Aluminium	Aluminium	Aluminium	
Omgivelsestemperatur:	Max 35°	Max 35°	Max 35°	
Kapslingsklasse:	IP20	IP20	IP20	
Netfrekvens:	50Hz	50Hz	50Hz	
Farvegengivelse:	CRI >90	CRI >90	CRI >90	
Spænding:	220-240V	220-240V	220-240V	
Energiklasse:	A++ - A	A++ - A	A++ - A	
Driver:	Integreret	Integreret	Integreret	
Dæmpning:	Ja	Ja	Ja	
Dæmpemetode:	DALI*	DALI*	DALI*	
Middellevetid:	50.000 timer	50.000 timer	50.000 timer	
Vægt:	4 kg	10 kg	23 kg	
Dimensioner (mm):	Ø:350 x H:93	Ø:600 x H:93	Ø:900 x H:93	
Montage:	Direkte på loft eller væg	Direkte på loft eller væg	Direkte på loft eller væg	
Produkt nummer:	Hvid 3000K Hvid / 4000K Sort / 3000K Sort / 4000K	24-0300-000141 24-0300-000142 24-0300-000143 24-0300-000144	24-0300-000145 24-0300-000146 24-0300-000147 24-0300-000148	24-0300-000149 24-0300-000150 24-0300-000151 24-0300-000152

*Kan på forespørgsel bestilles med 1-10V



LIGHT INNOVATION TECHNOLOGY

MÅL OG SPECIFIKATIONER

