



RIDE SURFACE

Ekstruderet aluminium LED profil i anodiseret sølv eller hvid finish. Høj farvegengivelse i et energibesparende og minimalistisk armatur. Ride Surface kan bestilles med 2 eller 3 spots.

GENEREL INFORMATION

	2 spots	3 spots	
Systemeffekt:	6W	8W	
Spredningsvinkel:	Spot 16° (Medium 30° ved bestilling)	Spot 16° (Medium 30° ved bestilling)	
Farvetemperatur:	2700 / 3000 / 4000K	2700 / 3000 / 4000K	
Total lysstrøm:	180 / 190 / 220lm	270 / 290 / 330lm	
Armaturvirkningsgrad:	30 / 32 / 37lm/W	34 / 36 / 41lm/W	
Armaturfarve:	<input type="checkbox"/> H <input type="checkbox"/> A	<input type="checkbox"/> H <input checked="" type="checkbox"/> S <input type="checkbox"/> A	
Armaturmateriale:	Ekstruderet aluminium profil	Ekstruderet aluminium profil	
Kapslingsklasse:	IP20	IP20	
Isolationsklasse:	Klasse I	Klasse I	
Netfrekvens:	50Hz	50Hz	
CRI:	>80	>80	
Spænding:	220-240VAC	220-240VAC	
Energi forbrug:	7kWh pr. 1000 brændetimer	9kWh pr. 1000 brændetimer	
Energiklasse:	A	A	
Chip:	MacAdam3	MacAdam3	
Driver:	Integreret	Integreret	
Dæmpning:	Nej	Nej	
Middellevetid L80B10:	50.000 timer	50.000 timer	
Dimension:	L: 427 x H:35 x B:35	L: 637 x H:35 x B:35	
Produkt nr:	Spot 16° / 2700K / Hvid Spot 16° / 2700K / Alu Spot 16° / 2700K / Sort Spot 16° / 3000K / Hvid Spot 16° / 3000K / Alu Spot 16° / 3000K / Sort Spot 16° / 4000K / Hvid Spot 16° / 4000K / Alu Spot 16° / 4000K / Sort	24-0300-000200 24-0300-000203 - 24-0300-000201 24-0300-000204 - 24-0300-000202 24-0300-000205 -	24-0300-000206 24-0300-000209 24-0300-000212 24-0300-000207 24-0300-000210 24-0300-000213 24-0300-000208 24-0300-000211 24-0300-000214



MÅL

